

Package ‘cmhc’

July 22, 2025

Type Package

Title Access, Retrieve, and Work with CMHC Data

Version 0.2.10

Description

Wrapper around the Canadian Mortgage and Housing Corporation (CMHC) web interface. It enables programmatic and reproducible access to a wide variety of housing data from CMHC.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

ByteCompile yes

NeedsCompilation no

Depends R (>= 4.1)

Imports dplyr (>= 1.0), digest (>= 0.1), httr, readr, stringr, tibble, rlang, aws.s3

Suggests knitr, scales, cencensus, ggplot2, tidyr, rmarkdown, sf

VignetteBuilder knitr

URL <https://github.com/mountainMath/cmhc>,

<https://mountainmath.github.io/cmhc/>,

<https://www03.cmhc-schl.gc.ca/hmip-pimh/en>

BugReports <https://github.com/mountainMath/cmhc/issues>

RoxygenNote 7.3.1

Author Jens von Bergmann [aut, cre]

Maintainer Jens von Bergmann <jens@mountainmath.ca>

Repository CRAN

Date/Publication 2025-02-04 04:00:02 UTC

Contents

| | |
|--------------------------------|---|
| cmhc_quality_labels | 2 |
| get_cmhc | 2 |
| get_cmhc_geography | 4 |
| list_cmhc_breakdowns | 5 |
| list_cmhc_dimensions | 5 |
| list_cmhc_filters | 6 |
| list_cmhc_series | 7 |
| list_cmhc_surveys | 7 |
| list_cmhc_tables | 8 |
| select_cmhc_table | 8 |
| set_cmhc_cache_path | 9 |
| show_cmhc_cache_path | 9 |

| | |
|--------------|-----------|
| Index | 11 |
|--------------|-----------|

| | |
|---------------------|--|
| cmhc_quality_labels | <i>A list of CMHC quality indicators</i> |
|---------------------|--|

Description

Data obtained via this package will automatically translate internal CMHC quality labels using this translation vector, this named vector is useful when working with CMHC data obtained from other sources like sporadic excel sheets or data scraped from PDF reports.

Usage

```
cmhc_quality_labels
```

Format

A named vector to translate internal CMHC quality indicators to plain text.

| | |
|----------|---------------------------------------|
| get_cmhc | <i>Access CMHC data via the HMIP.</i> |
|----------|---------------------------------------|

Description

The data access needs to specify the survey, series, dimension (if any), and breakdown to specify the CMHC table to pull the data from. The 'list_cmhc_tables()' function can be used to list all the tables available via this package. Snapshot data needs to specify the year, or if it is monthly data the month. Time series data, i.e. when 'breakdown="Historical Time Series' is specified, does not need year or month parameters, but may have the frequency parameter set. Filters provide additional ways to filter the tables by sub-categories.

Usage

```

get_cmhc(
  survey,
  series,
  dimension,
  breakdown,
  geoFilter = "Default",
  geo_uid,
  year = NULL,
  quarter = NULL,
  month = NULL,
  frequency = NULL,
  filters = list(),
  refresh = FALSE
)

```

Arguments

| | |
|-----------|---|
| survey | The CMHC survey, one of "Scss", "Rms", "Srms", and "Seniors", consult 'list_cmhc_surveys()' for possible values. (Other surveys and more data series may be supported in future versions.) |
| series | The CMHC data series of the survey, consult 'list_cmhc_series()' for possible values. |
| dimension | The dimension to show in the results, consult 'list_cmhc_dimensions()' for possible values. |
| breakdown | The geographic breakdown, one of "Survey Zones", "Census Subdivision", "Neighbourhoods", "Census Tracts", if querying data for a snapshot in time or "Historical Time Periods" if querying time series data. Not all geographic breakdowns are available for all series. returns data frame with CMHC data, tile and subtitle are set as attributes. Consult 'list_cmhc_breakdowns()' for possible values. |
| geoFilter | optional geographic type, only relevant for provincial and Canada-wide tables. Options are "Default" (the default) which considers accesses the default tables which should be used for data at the metro area or finer geographies. The other designators are only useful when used in conjunction with 'geo_uid's for provinces or all of Canada. Specifying "All" will give data for all sub-regions, "Metro", which only considers data in metro areas, "50k" and "10k", which only considers data from metro areas and agglomerations with at least 50k or 10k people, respectively. |
| geo_uid | Census geographic identifier for which to query the data. Can be a census tract, census subdivision, or census metropolitan area. |
| year | optional, only needed when querying data for a snapshot in time. |
| quarter | optional, only needed when querying data for a snapshot in time querying quarterly data. |
| month | optional, only needed when querying data for a snapshot in time. |
| frequency | optional, only needed when querying time series data, one of "Monthly", "Quarterly" or "Annual". |

filters optional list of filters, consult 'list_cmhc_filters()' for possible values.
 refresh optional, refresh the temporary local cache of the CMHC tables. Defaults to 'FALSE'.

Value

A tibble with the data in long form.

Examples

```
## Not run:
data <- get_cmhc("Rms", "Vacancy Rate", "Bedroom Type", "Historical Time Periods", "5915022")

## End(Not run)
```

get_cmhc_geography *Get CMHC geographies for CMHC Survey Zones and Neighbourhoods*

Description

The data can be queried for Census Tracts, Survey Zones, Neighbourhoods, Census Subdivisions and Metropolitan Areas, but it's most useful for Survey Zones, Neighbourhoods which are particular to CMHC and not available from other sources. The geographic data corresponds to an extract from 2017, and won't necessarily match regions from other years. The Survey Zones and Neighbourhoods have been quite stable, but census geographies change over time and can be matched with geographic data obtained by using the 'cancensus' package.

The geographic data is quite large and a local cache directory needs to be provided. By default the "CMHC_CACHE_PATH" environment variable is used to determine the cache directory, it can be set via the 'set_cache_path' function. The geographic data will take up about 55Mb of disk space.

Usage

```
get_cmhc_geography(
  level = c("CT", "ZONE", "NBHD", "CSD", "MET"),
  base_directory = Sys.getenv("CMHC_CACHE_PATH")
)
```

Arguments

level aggregation level for geographic data, one of "CT", "ZONE", "NBHD", "CSD", "MET"
 base_directory local directory to hold CMHC geography data, by default this is inferred from the CMHC_CACHE_PATH environment variable. To use this function a local data directory has to be set.

Value

A spatial data frame with the geographies for the specified geographic level.

Examples

```
## Not run:  
get_cmhc_geography("ZONE")  
  
## End(Not run)
```

```
list_cmhc_breakdowns List available CMHC breakdowns
```

Description

List available CMHC breakdowns

Usage

```
list_cmhc_breakdowns(survey = NULL, series = NULL, dimension = NULL)
```

Arguments

| | |
|-----------|---------------------------------|
| survey | Optional survey to filter by |
| series | Optional series to filter by |
| dimension | Optional dimension to filter by |

Value

A data frame with survey names, series names, dimension names and available series breakdowns.

Examples

```
list_cmhc_breakdowns("Rms", "Vacancy Rate", "Bedroom Type")
```

```
list_cmhc_dimensions List available CMHC dimensions
```

Description

List available CMHC dimensions

Usage

```
list_cmhc_dimensions(survey = NULL, series = NULL)
```

Arguments

| | |
|--------|------------------------------|
| survey | Optional survey to filter by |
| series | Optional series to filter by |

Value

A data frame with survey names, series names, and available dimension names.

Examples

```
list_cmhc_dimensions("Rms", "Vacancy Rate")
```

| | |
|-------------------|------------------------------------|
| list_cmhc_filters | <i>List available CMHC filters</i> |
|-------------------|------------------------------------|

Description

List available CMHC filters

Usage

```
list_cmhc_filters(
  survey = NULL,
  series = NULL,
  dimension = NULL,
  breakdown = NULL
)
```

Arguments

| | |
|-----------|---------------------------------|
| survey | Optional survey to filter by |
| series | Optional series to filter by |
| dimension | Optional dimension to filter by |
| breakdown | Optional breakdown to filter by |

Value

A data frame with available filters

Examples

```
list_cmhc_filters("Rms", "Vacancy Rate", "Bedroom Type", "Historical Time Periods")
```

| | |
|------------------|-----------------------------------|
| list_cmhc_series | <i>List available CMHC series</i> |
|------------------|-----------------------------------|

Description

List available CMHC series

Usage

```
list_cmhc_series(survey = NULL)
```

Arguments

survey Optional survey to filter by

Value

A data frame with survey names, and available series names.

Examples

```
list_cmhc_series("Rms")
```

| | |
|-------------------|------------------------------------|
| list_cmhc_surveys | <i>List available CMHC surveys</i> |
|-------------------|------------------------------------|

Description

List available CMHC surveys

Usage

```
list_cmhc_surveys()
```

Value

A data frame with available survey names.

Examples

```
list_cmhc_surveys()
```

| | |
|------------------|-----------------------------------|
| list_cmhc_tables | <i>List available CMHC tables</i> |
|------------------|-----------------------------------|

Description

List available CMHC tables

Usage

```
list_cmhc_tables(short = TRUE)
```

Arguments

short Logical, determines how much detail is returned. Default is 'TRUE'.

Value

A tibble listing all available CMHC data tables

Examples

```
list_cmhc_tables()
```

| | |
|-------------------|-----------------------------------|
| select_cmhc_table | <i>Interactive table selector</i> |
|-------------------|-----------------------------------|

Description

Interactive table selector

Usage

```
select_cmhc_table()
```

Value

A string containing the function call to access the selected table

Examples

```
## Not run:  
select_cmhc_table()  
  
## End(Not run)
```

set_cmhc_cache_path *Set persistent cmhc cache location for geographic data*

Description

The cmhc package provides access to custom cmhc geographies, these are large files and should be stored in a permanent location. This function sets the CMHC_CACHE_PATH environment variable and optionally installs it in the .Renvron file for future use. This is only needed when using the 'get_cmhc_geography()' function.

Usage

```
set_cmhc_cache_path(cache_path, overwrite = FALSE, install = FALSE)
```

Arguments

| | |
|------------|---|
| cache_path | a local directory to use for saving cached data |
| overwrite | Option to overwrite any existing cache path already stored locally. |
| install | Option to install permanently for use across sessions. |

Value

a character string with the CMHC cache path

Examples

```
## Not run:  
# This sets the cache path for the duration of the current session  
set_cmhc_cache_path("~/cmhc_cache")  
  
# This will set the cache path permanently until overwritten again  
set_cmhc_cache_path("~/cmhc_cache", install = TRUE)  
  
## End(Not run)
```

show_cmhc_cache_path *View saved cache directory path*

Description

View saved cache path

Usage

```
show_cmhc_cache_path()
```

10

show_cmhc_cache_path

Value

a character string with the CMHC cache path

Examples

`show_cmhc_cache_path()`

Index

- * **API**
 - get_cmhc, 2
- * **CMHC**
 - get_cmhc, 2
- * **Canada**
 - get_cmhc, 2
- * **datasets**
 - cmhc_quality_labels, 2
- * **data**
 - get_cmhc, 2

cmhc_quality_labels, 2

get_cmhc, 2

get_cmhc_geography, 4

list_cmhc_breakdowns, 5

list_cmhc_dimensions, 5

list_cmhc_filters, 6

list_cmhc_series, 7

list_cmhc_surveys, 7

list_cmhc_tables, 8

select_cmhc_table, 8

set_cmhc_cache_path, 9

show_cmhc_cache_path, 9